




# ARMATEUR LED



### Main features:

- Insulated Conductor, Aluminum Base, Epistar 3030 Chip
- Professional air convection design for best heat dissipation
- Ultra low power consumption
- IP65.3 years warranty or 5 years warranty

PF

>0.95



≥70



30000

## UF 06 SERIES

Model	Power	Voltage	Lumen	CCT	Size
UF 06	50W	AC100-240V	5000LM	2700-6500K	φ230*155MM
UF 06	100W	AC100-240V	10000LM	2700-6500K	φ310*167MM
UF 06	150W	AC100-240V	15000LM	2700-6500K	φ360*180MM
UF 06	200W	AC100-240V	20000LM	2700-6500K	φ410*185MM



### Main features:

- Insulated Conductor, Aluminum Base, Epistar 3030 Chip
- Professional air convection design for best heat dissipation
- Ultra low power consumption
- IP65.3 years warranty or 5 years warranty

PF

>0.95



≥70



30000

## UFO01 SERIES

Model	Power	Voltage	Lumen	Beam Angle	CCT	Size
UFO01-1	100W	AC100-240V	10000LM	120°	2700-6500K	φ240*200MM
UFO01-2	150W	AC100-240V	15000LM	120°	2700-6500K	φ300*210MM
UFO01-3	200W	AC100-240V	20000LM	120°	2700-6500K	φ350*210MM