



Ref.	51533
Colección / Collection	Technical Indoor. Arquitectural
Descripción / Description	Downlight Empotrable Fijo Redondo / Recessed Downlight Fixed Round
Material	Aluminio / Aluminium
Colores / Colours	01 Negro / Black 90 Blanco Téc. / Tec. White
Wattios / System Power	30W
Lumens	51533-2963 2900 lm 51533-2964 3045 lm 51533-2966 3197 lm
Tipo LED / Lighting Source Type	EPISTAR COB
Temperatura de Color / Color Temperature	51533-2963 3000K 51533-2964 4000K 51533-2966 6000K
IRC / CRI (Ra)	>80
Grados Apertura / Openning Degrees	60°
IP ext	44
IP int	20
Acabado Óptica / Difusor Finish	ACID
Material Óptica / Difusor Material	CRISTAL
Driver Externo / External Driver	JISO - INCLUDED
Corriente trabajo / Working Current	850 mA
Input Voltage	AC100-240V 50/60Hz
Factor de Potencia / PF	>0,9
Vida Útil / Service Life	30.000 H.
Garantía / Warranty	2 Years
Operating Temper.	-20°C TO +45°C
Working Humidity	20-90% RH
Diametro Exterior / Ext. Diameter	225 mm
Altura / Height	53 mm
Corte de techo / Ceiling Cut	200 mm
Peso / Weight Kg	0,80
Pcs/Ctn	1/20

OTRAS OPCIONES / OTHER OPTIONS

Consultar pedido mínimo, precio y plazo / Please consult MOQ, price and delivery time

Otro Driver / Other Driver	ELT / BOKE
Driver Dimmable	1-10V / Dali / Push
Kit Emergencia / Emergency Kit	Yes
Bluetooth	Yes