



Ref.	54722
Colección / Collection	Technical Indoor. Architectural
Descripción / Description	Downlight redondo LED Triple encendido Downlight round LED Three Lights
Material	Aluminio / Aluminium
Colores / Colours	90-Blanco Téc. / Tec. White
Wattios / System Power	15W + 7W
Lumens	54722-2983 1608 lm 54722-2984 1693 lm
Tipo LED / Lighting Source Type	GENESIS COB + EPISTAR SMD
Temperatura de Color / Color Temperature	54722-2983 3000K 54722-2984 4000K
IRC / CRI (Ra)	>80
Grados Apertura / Opening Degrees	120°
IP	20
Acabado Óptica / Difusor Finish	Si / Yes
Material Óptica / Difusor Material	PMMA ACRYLIC
Driver Externo / External Driver	JISO - INCLUDED
Corriente trabajo / Working Current	300 mA
Input Voltage	AC100- 240V 50-60Hz
Factor de Potencia / PF	>0,5
Vida Útil / Service Life	30.000 H.
Garantía / Warranty	2 Years
Operating Temper.	-20°C to +45°C
Working Humidity	20-85% RH
Diametro Exterior / Ext. Diameter	180 mm
Altura / Height	35 mm
Corte de techo / Ceiling Cut	160 mm
Peso / Weight Kg	0,45
Pcs/Ctn	1/20

